

**Pinces - Spannzangen - Collets ESX, EX**
**ESX (DIN 6499-B)**


**qualité standard**  
**Qualität Standard**  
**quality standard**

**avec plage de serrage (S) vers le bas**  
**mit Spannbereich (S) nach unten**  
**with compression (S) inwards**

**EX (DIN 6499-A)**


**qualité UP**  
**Qualität UP**  
**quality UP**

**serre le diamètre nominal**  
**spannt den Nenndurchmesser**  
**clamps the nominal diameter**

Gr.	Art.	D1	D2	L	S	Gr.	Art.	D1	D2	L
ESX9	<b>75-9300</b>	9	1-5	14.5	0.5	EX9	<b>75-9200</b>	9	0.5-5	14.5
ESX12	<b>75-12300</b>	12	1-3 4-7	19.5	0.5 1	EX12	<b>75-12200</b>	11.75	0.5-7	17.5
ESX16	<b>75-16300</b>	17	1-1.5 2-10	27.5	0.5 1	EX16	<b>75-16200</b>	16.7	0.3-10	27.5
DIN 6499-B						DIN 6499-A				
ESX20	<b>75-20300</b>	21	1-1.5 2-13	31.5	0.5 1	EX20	<b>75-20200</b>	20.7	1-13	31.5
DIN 6499-B						DIN 6499-A				
ESX25	<b>75-25300</b>	26	1-1.5 2-16	34	0.5 1	EX25	<b>75-25200</b>	25.7	1-16	34
DIN 6499-B						DIN 6499-A				
ESX32	<b>75-32300</b>	33	2.5 3-20	40	0.5 1	EX32	<b>75-32200</b>	32.7	2-20	40
DIN 6499-B						DIN 6499-A				
ESX40	<b>75-40300</b>	41	3-26	46	1	EX40	<b>75-40200</b>	40.7	3-26	46
DIN 6499-B						DIN 6499-A				