

Pinces tirées - Zugspannzangen - Pull-type collets



Obtrateurs pour pinces, voir page 70
Dichtgummi für Spannzangen auf Seite 70
Rubber seals for collets on page 70

| Type | Art. | A | B | C | G | α | D min-max | L | Fig. |
|--------------|---------|------|------|------|----------|-----|--------------|------|------|
| P4.5 | 78-153 | 4.5 | 6.75 | 22.9 | M3.35 | 15° | 0.30...2.50 | - | 1 |
| | | | | | | | 2.51...3.00 | 8.5 | |
| | | | | | | | 3.01...4.00 | 4 | |
| | | | | | | | 4.01...4.50 | 3 | |
| P5 | 78-154 | 5 | 7 | 22.9 | M3.5 | 15° | 0.30...2.70 | - | 1 |
| | | | | | | | 2.71...3.00 | 8.5 | |
| | | | | | | | 3.01...3.50 | 12 | |
| | | | | | | | 3.51...4.00 | 4 | |
| | | | | | | | 4.01...4.50 | 3 | |
| P6 | 78-150 | 6 | 8.5 | 27.2 | M4 | 15° | 0.30...3.20 | - | 1 |
| | | | | | | | 3.21...4.50 | 11.5 | |
| | | | | | | | 4.51...5.00 | 4.5 | |
| P6 | 78-155 | 6 | 8.5 | 24.1 | M4 | 20° | 0.30...3.20 | - | 1 |
| | | | | | | | 3.21...4.50 | 8.5 | |
| | | | | | | | 4.51...5.00 | 3.5 | |
| P9 | 78-157 | 9 | 13.2 | 39.3 | M6 | 15° | 0.30...4.70 | - | 1 |
| | | | | | | | 4.71...7.00 | 24 | |
| | | | | | | | 7.01...8.00 | 7 | |
| | | | | | | | 8.01...9.00 | 5 | |
| P10 | 78-228 | 10 | 14 | 39 | M7 | 15° | 0.30...5.70 | - | 1 |
| | | | | | | | 5.71...8.00 | 21.5 | |
| | | | | | | | 8.01...8.50 | 6 | |
| | | | | | | | 8.51...9.00 | 5 | |
| | | | | | | | 9.01...9.50 | 4 | |
| 9.51...10.00 | 3 | | | | | | | | |
| P25 | 78-334 | 25 | 35 | 75 | M22x1 | 16° | 0.50...18.26 | - | 2 |
| PR28 | 78-2013 | 28 | 32 | 73 | - | 8° | 2.00...24.50 | - | 3 |
| PR35.5 | 78-2012 | 35.5 | 40 | 80 | - | 8° | 2.00...30.00 | - | 3 |
| P36 | 78-2007 | 36 | 45 | 107 | M33x1.25 | 16° | 2.00...21.00 | - | 2 |

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.