

Pinces tirées - Zugspannzangen - Pull-type collets



Alésage à cran
 Stufenbohrung
 Step bore

Obtrateurs pour pinces, voir page 70
 Dichtgummi für Spannzangen auf Seite 70
 Rubber seals for collets on page 70

| Type | Art. | A | B | C | G | α | D min-max | L | Fig. |
|--------------|---------|------|------|------|----------|----------|--------------|------|------|
| P4.5 | 78-153 | 4.5 | 6.75 | 22.9 | M3.35 | 15° | 0.30...2.50 | - | 1 |
| | | | | | | | 2.51...3.00 | 8.5 | |
| | | | | | | | 3.01...4.00 | 4 | |
| | | | | | | | 4.01...4.50 | 3 | |
| P5 | 78-154 | 5 | 7 | 22.9 | M3.5 | 15° | 0.30...2.70 | - | 1 |
| | | | | | | | 2.71...3.00 | 8.5 | |
| | | | | | | | 3.01...3.50 | 12 | |
| | | | | | | | 3.51...4.00 | 4 | |
| | | | | | | | 4.01...4.50 | 3 | |
| P6 | 78-150 | 6 | 8.5 | 27.2 | M4 | 15° | 0.30...3.20 | - | 1 |
| | | | | | | | 3.21...4.50 | 11.5 | |
| | | | | | | | 4.51...5.00 | 4.5 | |
| | 78-155 | 6 | 8.5 | 24.1 | M4 | 20° | 0.30...3.20 | - | 1 |
| | | | | | | | 3.21...4.50 | 8.5 | |
| P9 | 78-157 | 9 | 13.2 | 39.3 | M6 | 15° | 0.30...4.70 | - | 1 |
| | | | | | | | 4.71...7.00 | 24 | |
| | | | | | | | 7.01...8.00 | 7 | |
| | | | | | | | 8.01...9.00 | 5 | |
| P10 | 78-228 | 10 | 14 | 39 | M7 | 15° | 0.30...5.70 | - | 1 |
| | | | | | | | 5.71...8.00 | 21.5 | |
| | | | | | | | 8.01...8.50 | 6 | |
| | | | | | | | 8.51...9.00 | 5 | |
| | | | | | | | 9.01...9.50 | 4 | |
| 9.51...10.00 | 3 | | | | | | | | |
| P25 | 78-334 | 25 | 35 | 75 | M22x1 | 16° | 0.50...18.26 | - | 2 |
| PR28 | 78-2013 | 28 | 32 | 73 | - | 8° | 2.00...24.50 | - | 3 |
| PR35.5 | 78-2012 | 35.5 | 40 | 80 | - | 8° | 2.00...30.00 | - | 3 |
| P36 | 78-2007 | 36 | 45 | 107 | M33x1.25 | 16° | 2.00...21.00 | - | 2 |

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.